



<p>[E] 溫度,風扇訊號接頭 (6Pin)</p> <p>1 KTY84~130 + (馬達溫度)</p> <p>2 KTY84~130 - (馬達溫度)</p> <p>3 PTC130 + (馬達溫度)</p> <p>4 PTC130 - (馬達溫度)</p> <p>5 散熱風扇 + DC24V(0.43A)</p> <p>6 散熱風扇 - DC24V(0.43A)</p> <p>附件 主軸開口鉸手 ER32 螺帽開口鉸手</p>	<p>刀具規格</p> <p>筒夾ER 32 夾持刀具尺寸$\phi 2.0 \sim \phi 20$</p> <p>螺帽ER 32 (M40*P1.5)</p> <p>[AS] 前端氣幕入口 1~1.5 bar M5*P0.8 $\phi 4$管徑</p> <p>[EP] 馬達電纜線出線 (U.V.W.G) M25*P1.5-3/4"浪管</p> <p>[E] 溫度,風扇,訊號接頭 6 pin</p>
--	--

馬達極數 4 極		S1/100Z					S1/100Z				
連續功率		Y					A				
馬達繞線規格											
電壓 [V]	380	380	380	380	380	220	220	220	220	220	
電流 [A]	24	20.2	19.4	17.2	6	42	35.1	33.7	30.8	10.5	
頻率 [Hz]	234	400	534	667	800	234	400	534	667	800	
轉速 [rpm]	7,000	12,000	16,000	20,000	24,000	7,000	12,000	16,000	20,000	24,000	
功率 [kw]	10	10	10	9	2.1	10	10	10	10	2.1	
轉距 [Nm]	13.9	8.1	6	4.3	0.8	13.9	8.1	6	4.3	0.8	
Itemref	Quantity	Title/Name, designation, material, dimension etc							Article No./Reference		
Designed by	Checked by	Approved by - date			Filename	Date	Scale				
		Name	WLR120g-D(10kw)								
		Number	W95.09D.024.WLR	Edition	Sheet						